



tesa® 4288

Product Information



Medium-duty Tensilized Strapping Tape

Product Features

- tesa® 4288 exhibits high tensile strength with low elongation at the same time.
- The applied product is heat- and cold-resistant, due to the black backing's resistance to UV-light.
- The natural rubber adhesive features a high tack, a short dwell time until reaching its final adhesive strength, and excellent adhesiveness to various substrates, including polar and non-polar surfaces.
- After use, the tape offers a residue-free removal and will leave no discoloration.

tesa® 4288 is a stable, medium-duty polypropylene strapping tape with a natural rubber adhesive system.

Application Fields

- tesa® 4288 is used in a wide variety of industrial applications: bundling of copper, bundling of iron and plastic pipes, palletizing, unitizing, and coil tabbing.
- The strapping tape is temperature- and UV-resistant.
- tesa® 4288 features residue-free removal.

Product Construction

- | | | | |
|--------------------|----------------|--------------------|------|
| • Type of adhesive | natural rubber | • Backing material | MOPP |
| • Total thickness | 114 µm | | |

Product Properties/Performance Values

- | | | | |
|--------------------|----------|------------------------|-----|
| • Tensile strength | 300 N/cm | • Residue free removal | Yes |
| • No discoloration | Yes | | |



tesa[®] 4288

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=04288>