



# tesa® 51134

## Product Information



Surface protection film for the protection of various surfaces mainly in the automotive interior

### Product Features

- Transparent film with higher adhesion
- Good adhesion and traceless removal
- Versatile with regard to use on surfaces like PP, ABS, and textiles
- Cost saving due to reduction in rectification and final repair
- No special equipment needed, ensuring simple, low-cost application and removal processes
- Easy disposal. Both film and adhesive system are environmentally friendly

tesa® 51134 is a self-adhesive film that has been developed for the protection of various surfaces, especially interior parts of automobiles like dashboards and door sills during storage, assembly, and transportation.

tesa® 51134 is a transparent self-adhesive polyethylene tape with an acrylic adhesive

### Application Fields

tesa® 51134 is suitable for the protection of various surfaces in the automotive interior made of plastic or textiles like dashboards and door sills against dirt and damage during storage, assembly, and transportation.

### Product Construction

- |                    |         |                    |         |
|--------------------|---------|--------------------|---------|
| • Type of adhesive | acrylic | • Backing material | PE film |
| • Total thickness  | 84 µm   |                    |         |

### Product Properties/Performance Values

- |                          |         |                  |     |
|--------------------------|---------|------------------|-----|
| • Tensile strength       | 15 N/cm | • Easy to remove | Yes |
| • Temperature resistance | 90 °C   |                  |     |



# tesa<sup>®</sup> 51134

## Product Information

### Disclaimer

tesa<sup>®</sup> products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa<sup>®</sup> product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit  
<http://l.tesa.com/?ip=51134>