



tesa[®] 53949 Matt Gaffer Tape



Product Information

Non-reflective polyethylene coated high grade cloth tape

Product Features

- light-absorbing, non-reflective
- good adhesion, even on rough surfaces
- abrasion resistant
- water repellent
- conformable
- easy to remove

tesa[®] 53949 is a matt gaffer tape specially designed for the arts and entertainment industry. It consists of a PE coated 80 mesh woven PET fabric backing coated with a pressure sensitive natural rubber adhesive.

tesa[®] 53949 is the ideal solution for a wide range of applications whenever a non-reflective surface is important.

Application Fields

- On-stage/back-stage jobs in theatre, opera, cinema and music halls
- Fixing of cables on carpets, walls etc.
- Covering of shiny and glossy surfaces
- Fixing of cable links
- Sealing of joints
- Floor marking and fixing

Product Construction

- | | | | |
|-------------------|--------|--------------------|-------------------|
| • Total thickness | 310 µm | • Backing material | PE extruded cloth |
|-------------------|--------|--------------------|-------------------|

Product Properties/Performance Values

- | | | | |
|------------------------------|------|--------------------|--------------------------|
| • Elongation at break | 14 % | • Tensile strength | 85 N/cm |
| • Straight tear edges | + | • Mesh | 80 count per square inch |
| • backing appearance(visual) | matt | | |

Adhesion to Values

- | | |
|---------|----------|
| • steel | 1.6 N/cm |
|---------|----------|



tesa[®] 53949

Matt Gaffer Tape

Product Information

Disclaimer

tesa[®] products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa[®] product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=53949>