



tesa® 64500

Product Information



special transport securing tape

Product Features

- High moisture and humidity resistance
- High conformability to different shapes and abrasion resistance
- High stability of backing
- Residue-free removability from a variety of different surfaces without discoloration

tesa® 64500 consists of a tensilised polypropylene backing with enhanced cross stability and a special natural rubber adhesive system.

Application Fields

Transport securing and surface protection of components in various industries, e.g. Office Automation and Appliances, etc. Suitable for long distant transport securing application even under challenging climate conditions.

Product Construction

- | | | | |
|--------------------|----------------|--------------------|------|
| • Type of adhesive | natural rubber | • Backing material | MOPP |
| • Total thickness | 110 µm | | |

Product Properties/Performance Values

- | | |
|--------------------|----------|
| • Tensile strength | 256 N/cm |
|--------------------|----------|

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=64500>