

tesa® 7496

product information



Premium Strength Tear Tape

Our strongest tensilized polypropylene backing with natural rubber adhesive. General-purpose tear tape has good initial tack, excellent shear resistance, and strong ultimate adhesion.

Available in a variety of lengths and widths for application flexibility. Available Colors: White

Main Application

- Heavy-duty tear tape for corrugated and solid board applications
- Handle and package reinforcement
- Durable surface protection

Technical Information (average values)

The values in this section should be considered representative or typical only and should not be used for specification purposes.

Technical Data

• Backing material	TPP	• Elongation at break	35 %
• Total thickness	172.5 µm	• Tensile strength	450 N/cm
• Type of adhesive	natural rubber		

Adhesion to

- steel 5.0 N/cm
45.7 oz/in

Disclaimer

tesa® products prove their impressive quality day in, day out in demanding conditions and are regularly subjected to strict controls. All information and recommendations are provided to the best of our knowledge on the basis of our practical experience. Nevertheless tesa SE can make no warranties, express or implied, including, but not limited to any implied warranty of merchantability or fitness for a particular purpose. Therefore, the user is responsible for determining whether the tesa® product is fit for a particular purpose and suitable for the user's method of application. If you are in any doubt, our technical support staff will be glad to support you.



For latest information on this product please visit
<http://l.tesa.com/?ip=07496>